

WX Series

PORTABLE GENERATOR



WE ARE **THE ENERGY** GENERATION





We generate **FREEDOM** for **WORKING**

PRAMAC PORTABLE GENERATORS RANGE: prompt power assistance to light up, tackle site jobs and property improvement works. A complete range to choose from, for best solution to your remote power needs. When not fixing up around the job site, your portable generator can be used for emergency power during a power outage.

	Frequency 50 Hz*				Frequency 60 Hz*				
	WX 3200	WX 6200	WX 6250	WX 7000	WX 1200	WX 3250	WX 5500	WX 6500	WX 8000
Three Phase Max Power			6100 Watts						
Three Phase Rated Power			5500 Watts						
Single Phase Max Power	2850 Watts	5800 Watts	2000 Watts	6100 Watts	1500 Watts	4050 Watts	6875 Watts	8125 Watts	10000 Watts
Single Phase Rated Power	2450 Watts	5300 Watts	1800 Watts	5800 Watts	1200 Watts	3250 Watts	5500 Watts	6500 Watts	8000 Watts
Voltage	230 V	230 V	230 V / 400 V	230 V	120 V	120 V	120 / 240 V	120 / 240 V	120 / 240 V
Running time at 50% of load	16.3 Hours	12 Hours	12 Hours	11.3 Hours	10 Hours	12.2 Hours	11 Hours	9.7 Hours	9.4 Hours
Tank Capacity	17 Litres	26 Litres	26 Litres	26 Litres	5.7 Litres	17 Litres	26 Litres	26 Litres	26 Litres
Fuel	Petrol	Petrol	Petrol	Petrol	Petrol	Petrol	Petrol	Petrol	Petrol
Displacement	208 cc	420 cc	420 cc	420 cc	98 cc	208 cc	420 cc	420 cc	445 cc
Speed	3000 rpm	3000 rpm	3000 rpm	3000 rpm	3600 rpm	3600 rpm	3600 rpm	3600 rpm	3600 rpm
Starting System	Recoil	Recoil	Recoil+ Electric	Recoil+ Electric	Recoil+ Electric	Recoil	Recoil	Recoil	Recoil+ Electric
Guaranteed sound level (LWA)	93 LWA	97 LWA	97 LWA	97 LWA					
Noise emission at 7 m	65 dB(A)	69 dB(A)	69 dB(A)	69 dB(A)					
Dimensions LxWxH (mm)	680x602x523 mm	800x698x620 mm	800x698x620 mm	800x698x620 mm	502x396x405 mm	676x599x516 mm	800x700x622 mm	800x700x622 mm	800x700x622 mm
Dry Weight	49 Kg	78 Kg 89 Kg	90 Kg	90 Kg	30 Kg	52.5 Kg	87 Kg	99.2 Kg	105 Kg
Socket type	2 x Schuko 230V 16A	2 x Schuko 230V 16A 1 x CEE 230V/32A	2 x Schuko 230V 16A 1 x CEE 400V 16A	2 x Schuko 230V 16A 1 x CEE 230V 32A	1 x DPLX 125V Nema 5-20R 12V DC lighter style outlet	2 x DPLX 125V Nema 5-20R 1 x TL 120V Nema L5-30R	2 x DPLX 125V Nema 5-20R 1 x TL 125/250V Nema L14-30R	2 x DPLX 125V Nema 5-20R 1 x TL 125/250V Nema L14-30R	2 x DPLX 125V Nema 5-20R 1 x TL 120V Nema L5-30R
Oil guard	✓	✓	✓	✓	✓	✓	✓	✓	✓
Fuel level gauge	✓	✓	✓	✓	✓	✓	✓	✓	✓
Thermal protection	✓	✓	✓	✓	✓	✓	✓	✓	✓
Hour meter	✓	✓	✓	✓	✓	✓	✓	✓	✓
Volt meter	✓	✓	✓	✓	✓	✓	✓	✓	✓
Frequency meter	✓	✓	✓	✓	✓	✓	✓	✓	✓
Wheel kit	✓	✓	✓	✓	✓	✓	✓	✓	✓

* Even available with UK sockets - 50Hz version and Brazilian sockets - 60Hz version



SUPPORT AT YOUR SERVICE



FLEXIBLE TRANSPORTABILITY



LONG LIFETIME

The **WX Series** portable generators provide power where and when you need it. These units deliver affordable reliability and are ideal for recreational or emergency home backup use.



PORTABILITY



OIL BOTTLE INCLUDED

dB
GUARANTEE

NOISE COMPLIANT



- A)** Two ergonomic handles fold down for easy storage
- B)** Fuel tank with fuel filter and fuel gauge
- C)** Control panel with digital display (Hourmeter / Voltmeter / Frequncymeter)

- D)** Roll cage design protects the generator
- E)** Wheels for easy transport
- F)** Low-oil level shutdown automatically safeguards engine from damage. Thermal Protection.



CONTROLLED QUALITY



USER FRIENDLY



TUTORIAL



**WE ARE
THE ENERGY
GENERATION**

Distributed by

For more information
visit us online at
www.pramac.com

PR INDUSTRIAL S.R.L.

Località Il Piano, 53031 Casole d'Elsa (SI) Italy
Tel. +39 0577 9651, Fax: +39 0577 949076
info@pramac.com / **www.pramac.com**

Worldwide Service & Parts
Online Center: **www.pramacparts.com**

© 2018 | PR INDUSTRIAL S.R.L. | All rights reserved
Image shown may not reflect actual package.
Specifications subject to change without notice.

